

# SAFETY DATA SHEET



AW Quantum Q-T260-80

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

**Product name** : AW Quantum Q-T260-80  
**Product code** : Q-T260-80

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Industrial surface coating for wood.  
Product is not intended for consumer use.

### 1.3 Details of the supplier of the safety data sheet

Akzo Nobel Hilden GmbH  
Düsseldorfer Straße 96-100  
D-40721 Hilden  
Deutschland  
Tel: (+49) 02103-77253  
Fax: (+49) 02103-77242  
Internet: <https://www.akzonobel.com/wood/>

**e-mail address of person responsible for this SDS** : [andrea.krause@akzonobel.com](mailto:andrea.krause@akzonobel.com)

#### National contact

Akzo Nobel Industrial Coatings Ltd  
Unit 04A Mercer Way  
Shadsworth Business Park  
Blackburn Lancashire  
United Kingdom  
BB1 2QZ

### 1.4 Emergency telephone number

#### Supplier

**Telephone number** : (+49) 02103-77253

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225  
Eye Irrit. 2, H319  
STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.  
See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

## SECTION 2: Hazards identification

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : Highly flammable liquid and vapour.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

### Precautionary statements

**Prevention** : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof [electrical/ventilating/lighting] equipment.

**Response** : IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

**Storage** : Keep cool.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** : n-butyl acetate

**Supplemental label elements** : Contains methyl methacrylate. May produce an allergic reaction.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### 2.3 Other hazards

**Other hazards which do not result in classification** : No additional information.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

| Product/ingredient name | Identifiers   | %         | <u>Classification</u><br>Regulation (EC) No. 1272/2008 [CLP]          | Type    |
|-------------------------|---|-----------|---|---------|
| n-butyl acetate         | REACH #:<br>01-2119485493-29<br>EC: 204-658-1<br>CAS: 123-86-4<br>Index: 607-025-00-1 | ≥25 - ≤50 | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>EUH066                       | [1] [2] |
| ethyl acetate           | REACH #:<br>01-2119475103-46<br>EC: 205-500-4<br>CAS: 141-78-6<br>Index: 607-022-00-5 | ≥10 - ≤25 | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336<br>EUH066 | [1] [2] |
| xylene                  | EC: 215-535-7<br>CAS: 1330-20-7<br>Index: 601-022-00-9                                | <10       | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332        | [1] [2] |

### SECTION 3: Composition/information on ingredients

|                     |  |      |  |         |
|---------------------|--|------|--|---------|
| ethylbenzene        | EC: 202-849-4<br>CAS: 100-41-4<br>Index: 601-023-00-4                                | ≤3   | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Flam. Liq. 2, H225<br>Acute Tox. 4, H332<br>STOT RE 2, H373 (hearing organs)                          | [1] [2] |
| methyl methacrylate | REACH #:<br>01-2119452498-28<br>EC: 201-297-1<br>CAS: 80-62-6<br>Index: 607-035-00-6 | ≤0.3 | Asp. Tox. 1, H304<br>Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>STOT SE 3, H335<br><br><b>See Section 16 for the full text of the H statements declared above.</b> | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

## SECTION 4: First aid measures

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains methyl methacrylate. May produce an allergic reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

**6.3 Methods and material for containment and cleaning up** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**7.1 Precautions for safe handling** : Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

**Information on fire and explosion protection**  
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

## SECTION 7: Handling and storage

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### 7.3 Specific end use(s)

**Recommendations** : No additional information.

**Industrial sector specific solutions** : No additional information.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name | Exposure limit values  |
|-------------------------|--|
| n-butyl acetate         | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b><br>STEL: 966 mg/m <sup>3</sup> 15 minutes.<br>STEL: 200 ppm 15 minutes.<br>TWA: 724 mg/m <sup>3</sup> 8 hours.<br>TWA: 150 ppm 8 hours.                        |
| ethyl acetate           | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b><br>STEL: 400 ppm 15 minutes.<br>TWA: 200 ppm 8 hours.  |
| xylene                  | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>STEL: 441 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 220 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours.  |
| ethylbenzene            | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>STEL: 552 mg/m <sup>3</sup> 15 minutes.<br>STEL: 125 ppm 15 minutes.<br>TWA: 441 mg/m <sup>3</sup> 8 hours.<br>TWA: 100 ppm 8 hours. |
| methyl methacrylate     | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b><br>STEL: 416 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 208 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours.                         |

## SECTION 8: Exposure controls/personal protection

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

| Product/ingredient name | Type | Exposure              | Value                 | Population | Effects  |
|-------------------------|------|-----------------------|-----------------------|------------|----------|
| n-butyl acetate         | DNEL | Short term Inhalation | 960 mg/m <sup>3</sup> | Workers    | Systemic |
|                         | DNEL | Short term Inhalation | 960 mg/m <sup>3</sup> | Workers    | Local    |
|                         | DNEL | Long term Inhalation  | 480 mg/m <sup>3</sup> | Workers    | Systemic |
|                         | DNEL | Long term Inhalation  | 480 mg/m <sup>3</sup> | Workers    | Local    |

### PNECs

| Product/ingredient name | Compartment Detail     | Value        | Method Detail |
|-------------------------|------------------------|--------------|---------------|
| n-butyl acetate         | Fresh water            | 0.18 mg/l    | -             |
|                         | Marine                 | 0.018 mg/l   | -             |
|                         | Fresh water sediment   | 0.981 mg/kg  | -             |
|                         | Marine water sediment  | 0.0981 mg/kg | -             |
|                         | Soil                   | 0.0903 mg/kg | -             |
|                         | Sewage Treatment Plant | 35.6 mg/l    | -             |

## 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.

### Skin protection

### Hand protection

## SECTION 8: Exposure controls/personal protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

Recommended (> 8 hours (breakthrough time)): polyvinyl alcohol (PVA), Viton®, polyethylene (PE)

May be used (4 - 8 hours (breakthrough time)): butyl rubber, nitrile rubber, neoprene

Not recommended (< 1 hour (breakthrough time)): polyvinyl chloride (PVC), PVC, natural rubber (latex)

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Wear a respirator conforming to EN140 with Type A/P2 filter or better.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

**Environmental exposure controls** : Do not allow to enter drains or watercourses.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

|   |                          |
|---|--------------------------|
| <b>Physical state</b>                               | : Liquid.                |
| <b>Colour</b>                                       | : Not available.         |
| <b>Odour</b>  | : Not available.         |
| <b>Odour threshold</b>                              | : Not applicable.        |
| <b>pH</b>   | : Not applicable.        |
| <b>Melting point/freezing point</b>                 | : Not tested             |
| <b>Initial boiling point and boiling range</b>      | : 74 - 143 °C            |
| <b>Flash point</b>                                  | : Closed cup: 4°C        |
| <b>Evaporation rate</b>                             | : Not tested             |
| <b>Flammability (solid, gas)</b>                    | : Not applicable.        |
| <b>Upper/lower flammability or explosive limits</b> | : Lower: 1% Upper: 11.5% |

## SECTION 9: Physical and chemical properties

|  |  |
|--|--|
| <b>Vapour pressure</b>                         | : 81.59 mm Hg (10.8515 kPa) (Highest known value: ethyl acetate) |
| <b>Vapour density</b>                          | : > 1 (Air = 1) (Calculation method)                             |
| <b>Density</b>                                 | : 0.93 g/cm <sup>3</sup>   |
| <b>Solubility(ies)</b>                         | : Not tested   |
| <b>Partition coefficient: n-octanol/ water</b> | : Not tested   |
| <b>Auto-ignition temperature</b>               | : 415 °C (Lowest known value: n-butyl acetate)                   |
| <b>Decomposition temperature</b>               | : Not tested   |
| <b>Viscosity</b>                               | : Not available.   |
| <b>Explosive properties</b>                    | : Not tested   |
| <b>Oxidising properties</b>                    | : Not tested   |

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

|  |  |
|--|--|
| <b>10.1 Reactivity</b>                         | : No specific test data related to reactivity available for this product or its ingredients.                                     |
| <b>10.2 Chemical stability</b>                 | : Stable under recommended storage and handling conditions (see Section 7).  |
| <b>10.3 Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.  |
| <b>10.4 Conditions to avoid</b>                | : When exposed to high temperatures may produce hazardous decomposition products.  |
| <b>10.5 Incompatible materials</b>             | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. |
| <b>10.6 Hazardous decomposition products</b>   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced.                           |

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

## SECTION 11: Toxicological information

Contains methyl methacrylate. May produce an allergic reaction.

### Acute toxicity

| Product/ingredient name | Result                 | Species | Dose                    | Exposure |
|-------------------------|------------------------|---------|-------------------------|----------|
| n-butyl acetate         | LD50 Dermal            | Rabbit  | >17600 mg/kg            | -        |
|                         | LD50 Oral              | Rat     | 10768 mg/kg             | -        |
| ethyl acetate           | LD50 Oral              | Rat     | 5620 mg/kg              | -        |
|                         | LC50 Inhalation Gas.   | Rat     | 5000 ppm                | 4 hours  |
| xylene                  | LD50 Oral              | Rat     | 4300 mg/kg              | -        |
|                         | LD50 Dermal            | Rabbit  | >5000 mg/kg             | -        |
| ethylbenzene            | LD50 Oral              | Rat     | 3500 mg/kg              | -        |
|                         | LC50 Inhalation Vapour | Rat     | 78000 mg/m <sup>3</sup> | 4 hours  |
| methyl methacrylate     | LD50 Dermal            | Rabbit  | >5 g/kg                 | -        |
|                         | LD50 Oral              | Rat     | 7872 mg/kg              | -        |

**Conclusion/Summary** : Not available.

### Acute toxicity estimates

| Route                | ATE value     |
|----------------------|---------------|
| Dermal               | 13297.9 mg/kg |
| Inhalation (gases)   | 60444.9 ppm   |
| Inhalation (vapours) | 709.2 mg/l    |

### Irritation/Corrosion

| Product/ingredient name | Result                   | Species | Score | Exposure                | Observation |
|-------------------------|--------------------------|---------|-------|-------------------------|-------------|
| n-butyl acetate         | Eyes - Moderate irritant | Rabbit  | -     | 100 milligrams          | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 milligrams | -           |
| xylene                  | Eyes - Mild irritant     | Rabbit  | -     | 87 milligrams           | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 5 milligrams   | -           |
|                         | Skin - Mild irritant     | Rat     | -     | 8 hours 60 microliters  | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 milligrams | -           |
| ethylbenzene            | Skin - Moderate irritant | Rabbit  | -     | 100 Percent             | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 500 milligrams          | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 15 milligrams  | -           |

**Conclusion/Summary** : Not available.

### Sensitisation

**Conclusion/Summary** : Not available.

### Mutagenicity

**Conclusion/Summary** : Not available.

### Carcinogenicity

**Conclusion/Summary** : Not available.

### Reproductive toxicity

**Conclusion/Summary** : Not available.

### Teratogenicity

**Conclusion/Summary** : Not available.

### Specific target organ toxicity (single exposure)

## SECTION 11: Toxicological information

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| n-butyl acetate         | Category 3 | Not applicable.   | Narcotic effects             |
| ethyl acetate           | Category 3 | Not applicable.   | Narcotic effects             |
| xylene                  | Category 3 | Not applicable.   | Respiratory tract irritation |
| methyl methacrylate     | Category 3 | Not applicable.   | Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs  |
|-------------------------|------------|-------------------|----------------|
| ethylbenzene            | Category 2 | Not determined    | hearing organs |

### Aspiration hazard

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| xylene                  | ASPIRATION HAZARD - Category 1 |
| ethylbenzene            | ASPIRATION HAZARD - Category 1 |

**Other information** : No additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

**Conclusion/Summary** : Not available.

### 12.2 Persistence and degradability

### 12.3 Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------|--------------------|-------------|-----------|
| n-butyl acetate         | 2.3                | -           | low       |
| ethyl acetate           | 0.68               | 30          | low       |
| xylene                  | 3.12               | 8.1 to 25.9 | low       |
| ethylbenzene            | 3.6                | -           | low       |
| methyl methacrylate     | 1.38               | -           | low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

**PBT** : Not applicable.

**vPvB** : Not applicable.

## SECTION 12: Ecological information

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of waste according to applicable legislation. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.





**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

| Type of packaging     | European waste catalogue (EWC)  |
|-----------------------|---|
| CEPE Paint Guidelines | 15 01 10*<br>packaging containing residues of or contaminated by hazardous substances |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

**SECTION 14: Transport information**

|  | ADR/RID  | ADN  | IMDG  | IATA   |
|--|--|--|---|--|
| <b>14.1 UN number</b>                  | UN1263   | UN1263   | UN1263  | UN1263   |
| <b>14.2 UN proper shipping name</b>    | PAINT  | PAINT  | PAINT   | PAINT  |
| <b>14.3 Transport hazard class(es)</b> | 3<br> | 3<br> | 3<br> | 3<br> |
| <b>14.4 Packing group</b>              | II   | II   | II  | II   |
| <b>14.5 Environmental hazards</b>      | No.  | No.  | No.   | No.  |
| <b>Additional information</b>          | <b>Special provisions</b><br>640 (C)<br><br><b>Tunnel code</b><br>(D/E)                | -  | -   | -  |

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** : Not applicable.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU Regulation (EC) No. 1907/2006 (REACH)****Annex XIV - List of substances subject to authorisation****Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

**Other EU regulations****Europe inventory** : Not determined.**Priority List Chemicals (793/93/EEC)** : Not determined**Seveso Directive**

## SECTION 15: Regulatory information

This product is controlled under the Seveso Directive.

### Danger criteria

#### Category

P5c: Flammable liquids 2 and 3 not falling under P5a or P5b

C7b: Highly flammable (R11)

### National regulations

#### Industrial use

: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

#### 15.2 Chemical safety assessment

: No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

#### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification  | Justification   |
|---|---|
| Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336 | On basis of test data<br>Calculation method<br>Calculation method |

#### Full text of abbreviated H statements

|                       |   |
|-----------------------|---|
| H225                  | Highly flammable liquid and vapour.   |
| H226                  | Flammable liquid and vapour.  |
| H304                  | May be fatal if swallowed and enters airways.                                       |
| H312                  | Harmful in contact with skin.   |
| H315                  | Causes skin irritation.   |
| H317                  | May cause an allergic skin reaction.  |
| H319                  | Causes serious eye irritation.  |
| H332                  | Harmful if inhaled.   |
| H335                  | May cause respiratory irritation.   |
| H336                  | May cause drowsiness or dizziness.  |
| H373 (hearing organs) | May cause damage to organs through prolonged or repeated exposure. (hearing organs) |

#### Full text of classifications [CLP/GHS]

|                     |   |
|---------------------|---|
| Acute Tox. 4, H312  | ACUTE TOXICITY (dermal) - Category 4                  |
| Acute Tox. 4, H332  | ACUTE TOXICITY (inhalation) - Category 4              |
| Asp. Tox. 1, H304   | ASPIRATION HAZARD - Category 1                        |
| EUH066              | Repeated exposure may cause skin dryness or cracking. |
| Eye Irrit. 2, H319  | SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2       |
| Flam. Liq. 2, H225  | FLAMMABLE LIQUIDS - Category 2                        |
| Flam. Liq. 3, H226  | FLAMMABLE LIQUIDS - Category 3                        |
| Skin Irrit. 2, H315 | SKIN CORROSION/IRRITATION - Category 2                |
| Skin Sens. 1, H317  | SKIN SENSITIZATION - Category 1                       |

## SECTION 16: Other information

|                                     |  |
|-------------------------------------|--|
| STOT RE 2, H373<br>(hearing organs) | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) - Category 2             |
| STOT SE 3, H335                     | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 |
| STOT SE 3, H336                     | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3             |

**Date of printing** : 2020-07-23

**Date of issue/ Date of revision** : 2020-02-13

**Date of previous issue** : 2020-01-23

**Version** : 1.39

### Notice to reader

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.