

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Name : Spabond 540LV Resin
Type of product : Epoxy resin
Product group : Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use
Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Gurit (UK) Ltd
St Cross Business Park
Newport
PO30 5WU Isle of Wight - United Kingdom
T +44 (0) 1983 828 000
regulatory@gurit.com - www.gurit.com

1.4. Emergency telephone number

Emergency number : Carechem 24: +44 (0) 1273 289451 24 Hours

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 1 H318
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

GHS07

GHS09

Signal word (CLP) :

Danger

Hazardous ingredients :

Formaldehyde, polymer with (chloromethyl)oxirane and phenol; reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700); oxirane, mono[(C12-14-alkyloxy)methyl] derivs.; 1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether

Hazard statements (CLP) :

H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P261 - Avoid breathing vapours.
P264 - Wash hands thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Spabond 540LV Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	\geq 50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	(CAS-No.) 68609-97-2 (EC-No.) 271-846-8 (EC Index-No.) 603-103-00-4 (REACH-no) 01-2119485289-22	5 - 10	Skin Irrit. 2, H315 Skin Sens. 1, H317
1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether	(CAS-No.) 2425-79-8 (EC-No.) 219-371-7 (EC Index-No.) 603-072-00-7 (REACH-no) 01-2119494060-45	5 - 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Formaldehyde, polymer with (chloromethyl)oxirane and phenol	(CAS-No.) 9003-36-5 (EC-No.) 500-006-8 (REACH-no) 01-2119454393-40	3 - 5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute Not classified Aquatic Chronic 2, H411

Specific concentration limits:

Name	Product identifier	Specific concentration limits
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	(C \geq 5) Skin Irrit. 2, H315 (C \geq 5) Eye Irrit. 2, H319

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing vapours.
----------------------	---

Spabond 540LV Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing vapours.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

Maximum storage period : 2 year

Storage temperature : ≤ 30 °C

Storage area : Store away from heat. Store in a well-ventilated place.

Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Safety glasses.

Hand protection:					
Protective gloves					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)				EN 374
Eye protection:					
Safety glasses					
Skin and body protection:					
Wear suitable protective clothing					
Type	Standard				
Tyvek® Gown/Coveralls	EN 13034				
Respiratory protection:					
In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended					
Device	Filter type	Condition	Standard		
Disposable half mask	Gas/vapour filter	Vapour protection	EN 405		

Spabond 540LV Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

Other information:

Industrial and professional. Perform risk assessment prior to use. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Paste.
Colour	: Yellow.
Odour	: characteristic.
Odour threshold	: No data available
pH	: ≈ 7
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 100 °C estimated
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not Applicable Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: Not applicable
Density	: 1.14 g/cm ³
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: 23684.211 mm ² /s
Viscosity, dynamic	: 27000 cP
Explosive properties	: Product is not explosive.
Oxidising properties	: No data available
Explosive limits	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Product is not explosive.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Spabond 540LV Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Acute toxicity (inhalation) : Not classified

Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)

LD50 oral rat > 2 g/kg

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

LD50 oral rat 11400 mg/kg

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

LD50 oral rat 17100 mg/kg

1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether (2425-79-8)

LD50 oral rat 1134 mg/kg

Skin corrosion/irritation : Causes skin irritation.
pH: ≈ 7

Serious eye damage/irritation : Causes serious eye damage.
pH: ≈ 7

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Spabond 540LV Resin

Viscosity, kinematic 23684.211 mm²/s

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)

LC50 fish 1 < 1 mg/l

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

LC50 fish 1 1.5 mg/l

LC50 fish 2 2 mg/l

12.2. Persistence and degradability

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

Persistence and degradability May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

Bioaccumulative potential Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

Spabond 540LV Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830




SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG

ADR	IMDG	IATA
14.1. UN number		
3077	3077	3077
14.2. UN proper shipping name		
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	Environmentally hazardous substance, solid, n.o.s.
Transport document description		
UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, polymer with (chloromethyl)oxirane and phenol), 9, III, (E)	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, polymer with (chloromethyl)oxirane and phenol), 9, III, MARINE POLLUTANT	UN 3077 Environmentally hazardous substance, solid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, polymer with (chloromethyl)oxirane and phenol), 9, III
14.3. Transport hazard class(es)		
9	9	9
		
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes
No supplementary information available		
14.6. Special precautions for user		

Overland transport

Classification code (ADR)	: M7
Special provisions (ADR)	: 274, 335, 601, 375
Limited quantities (ADR)	: 5kg
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P002, IBC08, LP02, R001
Special packing provisions (ADR)	: PP12, B3
Mixed packing provisions (ADR)	: MP10

Spabond 540LV Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Portable tank and bulk container instructions (ADR) : T1, BK1, BK2

Portable tank and bulk container special provisions (ADR) : TP33

Tank code (ADR) : SGAV, LGBV

Vehicle for tank carriage : AT

Transport category (ADR) : 3

Special provisions for carriage - Packages (ADR) : V13

Special provisions for carriage - Bulk (ADR) : VC1, VC2

Special provisions for carriage - Loading, unloading and handling (ADR) : CV13

Hazard identification number (Kemler No.) : 90

Orange plates :



Tunnel restriction code (ADR) : E

EAC code : 2Z

Transport by sea

Special provisions (IMDG) : 274, 335, 966, 967, 969

Limited quantities (IMDG) : 5 kg

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P002, LP02

Special packing provisions (IMDG) : PP12

IBC packing instructions (IMDG) : IBC08

IBC special provisions (IMDG) : B3

Tank instructions (IMDG) : T1, BK1, BK2, BK3

Tank special provisions (IMDG) : TP33

EmS-No. (Fire) : F-A

EmS-No. (Spillage) : S-F

Stowage category (IMDG) : A

Stowage and handling (IMDG) : SW23

Air transport

PCA Excepted quantities (IATA) : E1

PCA Limited quantities (IATA) : Y956

PCA limited quantity max net quantity (IATA) : 30kgG

PCA packing instructions (IATA) : 956

PCA max net quantity (IATA) : 400kg

CAO packing instructions (IATA) : 956

CAO max net quantity (IATA) : 400kg

Special provisions (IATA) : A97, A158, A179, A197

ERG code (IATA) : 9L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Directive 2012/18/EU (SEVESO III)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Spabond 540LV Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Full text of H- and EUH-statements:		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute Not classified	Hazardous to the aquatic environment - Acute Hazard Not classified	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
H302	Harmful if swallowed.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. The information contained within this document is Gurit copyright and any distribution or publication beyond the recipient's organisation is prohibited without Gurit's prior written consent.