

**SECTION 1: Identification of the substance/mixture and of the company/  
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes Epoxy Finishing Filler Component A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Product category  
PC9b Fillers, putties, plasters, modelling clay  
PC9a Coatings and paints, thinners, paint removers
- Process category  
PROC10 Roller application or brushing  
PROC5 Mixing or blending in batch processes
- Environmental release category ERC2 Formulation into mixture
- Application of the substance / the mixture  
See our technical datasheet for application of this product.  
base component of an epoxy based fine filler
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:  
W.Heeren & Zoon bv.  
P.O. box 166  
1430 AD Aalsmeer  
Netherlands  
tel.+31-(0)297-360366  
fax +31-(0)297-342078  
email: r&d@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number:  
W.Heeren & Zoon bv. tel: +31 297 360678, E-mail: rend@epifanes.nl  
Office hours: weekdays from 08:00 to 17:00.  
The National Poisons Information Service; dial 111  
Solely intended to inform professionals in acute poisoning!  
See manufacturer/supplier

**SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008  
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Trade name: Epifanes Epoxy Finishing Filler Component A

(Contd. of page 1)

· Hazard pictograms



GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labelling:

formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

1,6-bis(2,3-epoxypropoxy)hexane

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Contains epoxy constituents. May produce an allergic reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

<p>CAS: 9003-36-5 NLP: 500-033-5 Reg.nr.: 01-2119454392-40</p>	<p>formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol</p> <p>⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317</p>	<p>10-25%</p>
--	--	---------------

(Contd. on page 3)

Trade name: Epifanes Epoxy Finishing Filler Component A

(Contd. of page 2)

CAS: 16096-31-4 EINECS: 240-260-4 Reg.nr.: 01-2119463471-41	1,6-bis(2,3-epoxypropoxy)hexane ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412	10-25%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26	reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight = 700) ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-25%

- Additional information:  
For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:  
Immediately wash with water and soap and rinse thoroughly.  
Immediately rinse with water.
- After eye contact:  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed  
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

**SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:  
Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture  
During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

**SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures  
Mount respiratory protective device.
- 6.2 Environmental precautions:  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

Trade name: Epifanes Epoxy Finishing Filler Component A

(Contd. of page 3)

Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
· 6.4 Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
n.a.
- Information about fire - and explosion protection:  
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities  
· Storage:  
· Requirements to be met by storerooms and receptacles: No special requirements.  
· Information about storage in one common storage facility: Not required.  
· Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- Additional information about design of technical facilities:  
No further data; see item 7.
- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

9003-36-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Dermal	Acute-local effects, worker Long-term - systemic effects, worker	8.3 --- (Werker/Worker) 104.15 mg/kg bw/day (Werker/Worker)
Inhalative	Acute - systemic effects, worker	29.39 mg/kg (Werker/Worker)

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Dermal	Acute - systemic effects, worker Long-term - systemic effects, worker	8.3 mg/kg (Werker/Worker) 8.3 mg/kg bw/day (Werker/Worker)
Inhalative	Acute-local effects, worker Long-term - systemic effects, worker	12.3 mg/m <sup>3</sup> (Werker/Worker) 12.3 mg/m <sup>3</sup> (Werker/Worker)

(Contd. on page 5)

Trade name: Epifanes Epoxy Finishing Filler Component A

(Contd. of page 4)

· PNECs	
9003-36-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	
Aquatic compartment - freshwater	0.003 mg/L (Consument)
Aquatic compartment - marine water	0.0003 mg/L (4)
Aquatic compartment - water, intermittent releases	0.013 mg/L (intermittent release water)
Aquatic compartment - sediment in freshwater	0.294 mg/kg sed dw (3)
Aquatic compartment - sediment in marine water	0.0294 mg/kg sed dw (5)
Terrestrial compartment - soil	0.05 mg/kg dw (8)
Sewage treatment plant	10 mg/L (7)
25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)	
Aquatic compartment - freshwater	0.003 mg/L (Consument)
Aquatic compartment - marine water	0.0003 mg/L (4)
Aquatic compartment - water, intermittent releases	0.013 mg/L (intermittent release water)
Aquatic compartment - sediment in freshwater	0.5 mg/kg sed dw (3)
Aquatic compartment - sediment in marine water	0.5 mg/kg sed dw (5)
Terrestrial compartment - soil	0.05 mg/kg dw (8)
Sewage treatment plant	10 mg/L (7)

- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing
  - Wash hands before breaks and at the end of work.
  - Avoid contact with the eyes and skin.
- Respiratory protection:
  - Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Trade name: Epifanes Epoxy Finishing Filler Component A

(Contd. of page 5)

- Penetration time of glove material  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection:



Tightly sealed goggles

**SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:
  - Form: Solid
  - Colour: According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- pH-value at 20 °C: 7
- Change in condition
  - Melting point/freezing point: Undetermined.
  - Initial boiling point and boiling range: >200 °C
- Flash point: 151 °C
- Flammability (solid, gas): Not applicable.
- Ignition temperature: >370 °C
- Decomposition temperature: Not determined.
- Auto-ignition temperature: Product is not selfigniting.
- Explosive properties: Product does not present an explosion hazard.
- Explosion limits:
  - Lower: Not determined.
  - Upper: Not determined.
- Vapour pressure: Not determined.
- Density at 20 °C: 1.684 g/cm<sup>3</sup>
- Relative density: Not determined.
- Vapour density: Not determined.
- Evaporation rate: Not determined.
- Solubility in / Miscibility with water: Not miscible or difficult to mix.
- Partition coefficient: n-octanol/ water: Not determined.
- Viscosity:
  - Dynamic: Not determined.
  - Kinematic: Not determined.

(Contd. on page 7)

Trade name: Epifanes Epoxy Finishing Filler Component A

(Contd. of page 6)

- Solvent content:
  - Organic solvents: 0.0 %
  - VOC content: VOC content: 0.0 g/l / 0.00 lb/gl
- 9.2 Other information: No further relevant information available.

**SECTION 10: Stability and reactivity**

- 10.1 Reactivity: No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions: No dangerous reactions known.
- 10.4 Conditions to avoid: No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects
- Acute toxicity: Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

9003-36-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Oral	LD50	11400 mg/kg bw (rat)
Dermal	LD50	> 2000 mg/kg bw (rabbit)

16096-31-4 1,6-bis(2,3-epoxypropoxy)hexane

Oral	LD50	2900 mg/kg bw (rat)
Dermal	LD50	> 4900 mg/kg bw (rat)

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Oral	LD50	11400 mg/kg bw (rat)
Dermal	LD50	>2000 mg/kg bw (rabbit)

- Primary irritant effect:
  - Skin corrosion/irritation: Causes skin irritation.
  - Serious eye damage/irritation: Causes serious eye irritation.
  - Respiratory or skin sensitisation: May cause an allergic skin reaction.
  - CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
  - Germ cell mutagenicity: Based on available data, the classification criteria are not met.
  - Carcinogenicity: Based on available data, the classification criteria are not met.
  - Reproductive toxicity: Based on available data, the classification criteria are not met.

(Contd. on page 8)

Trade name: Epifanes Epoxy Finishing Filler Component A

(Contd. of page 7)

- STOT-single exposure  
Based on available data, the classification criteria are not met.
- STOT-repeated exposure  
Based on available data, the classification criteria are not met.
- Aspiration hazard  
Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Oral	EC50	1.1 - 3.6 mg/l ((Daphnia magna))
Inhalative	LC50/96 h	1.5 - 7.7 mg/l ((Regenboogforel))

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxicological effects:
- Remark: Toxic for fish
- Additional ecological information:
- General notes:  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

**SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

GB



(Contd. on page 9)



Trade name: Epifanes Epoxy Finishing Filler Component A

(Contd. of page 8)

**SECTION 14: Transport information**

<ul style="list-style-type: none"> <li>14.1 UN-Number</li> <li>ADR, IMDG, IATA</li> </ul>	<p>UN3082</p>
<ul style="list-style-type: none"> <li>14.2 UN proper shipping name</li> <li>ADR</li> <li>IMDG</li> <li>IATA</li> </ul>	<p>3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)</p> <p>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), MARINE POLLUTANT</p> <p>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)</p>
<ul style="list-style-type: none"> <li>14.3 Transport hazard class(es)</li> <li>ADR</li> </ul>	 <p>Class 9 (M6) Miscellaneous dangerous substances and articles.</p> <p>Label 9</p>
<ul style="list-style-type: none"> <li>IMDG, IATA</li> </ul>	 <p>Class 9 Miscellaneous dangerous substances and articles.</p> <p>Label 9</p>
<ul style="list-style-type: none"> <li>14.4 Packing group</li> <li>ADR, IMDG, IATA</li> </ul>	<p>III</p>
<ul style="list-style-type: none"> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> <li>Special marking (ADR):</li> <li>Special marking (IATA):</li> </ul>	<p>Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)</p> <p>Yes</p> <p>Symbol (fish and tree)</p> <p>Symbol (fish and tree)</p> <p>Symbol (fish and tree)</p>

(Contd. on page 10)

Trade name: Epifanes Epoxy Finishing Filler Component A

(Contd. of page 9)

- 14.6 Special precautions for user      Warning: Miscellaneous dangerous substances and articles.
- Danger code (Kemler):                      90
- EMS Number:                                  F-A,S-F
- Stowage Category                              A

- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

- Transport/Additional information:

- ADR
- Limited quantities (LQ)                      5L
- Excepted quantities (EQ)                      Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
- Transport category                              3
- Tunnel restriction code                        E

- IMDG
- Limited quantities (LQ)                      5L
- Excepted quantities (EQ)                      Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

- UN "Model Regulation":                      UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT = 700), FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, III

**SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment:  
A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 11)

Trade name: Epifanes Epoxy Finishing Filler Component A

(Contd. of page 10)

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

## · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

## · \* Data compared to the previous version altered.